



CR15wiNG

Future-ready Security with Wi-Fi Access Point for SOHO/ROBO networks

Data Sheet 

CR15wiNG is the Next-Generation Unified Threat Management appliance with Wi-Fi access points that offer “the fastest UTM’s made for SMBs” to small offices with high performance security over WLAN. CR15wiNG appliances come with 3x3 MIMO technology that greatly enhances wireless range and performance. It supports 802.11n/b/g wireless standards. Combined with security over wired networks offered by its range of UTM appliances, Cyberoam enables organizations to overcome the physical limitations of securely accessing network resources and offers more user flexibility, user productivity and lower network ownership costs.

The best-in-class hardware along with software to match, enables the NG series to offer unmatched throughput speeds, compared to any other UTM appliance in this market segment. This assures support for future IT trends in organizations like high-speed Internet and rising number of devices in organizations – offering future-ready security for small office networks.


Cyberoam’s Layer 8 technology that treats user-identity as the 8th Layer or the HUMAN layer in the protocol stack, works even in WLAN environments, to allow Identity-based security policies in dynamic IP environment.



The ‘Next-Generation’ UTM Series for SOHO:

Faster performance, broader coverage with 3x3 MIMO Technology



Cyberoam’s **Layer 8 Technology** treats “User Identity” as the 8th Layer in the protocol stack



L8	USER	
L7	Application	
L6	Presentation	ASCII, EBCDIC, ICA
L5	Session	L2TP, PPTP
L4	Transport	TCP, UDP
L3	Network	192.168.1.1
L2	Data Link	00-17-BB-8C-E3-E7
L1	Physical	

Cyberoam UTM offers security across Layer 2-Layer 8 using Identity-based policies

Cyberoam UTM features assure Security, Connectivity, Productivity

Security

Network Security

- Firewall
- Intrusion Prevention System
- Wireless Security

Content Security

- Anti-Virus/Anti-Spyware
- Anti-Spam (Inbound/Outbound)^{###}
- HTTPS/SSL Content Security

Administrative Security

- Next-Gen UI
- iView- Logging & Reporting



Connectivity

Business Continuity

- Multiple Link Management
- High Availability

Network Availability

- VPN
- 3G/4G/WiMAX Connectivity

Future-ready Connectivity

- “IPv6 Ready” Gold Logo



Productivity

Employee Productivity

- Content Filtering
- Instant Messaging Archiving & Controls

IT Resource Optimization

- Bandwidth Management
- Traffic Discovery
- Application Visibility & Control

Administrator Productivity

- Next-Gen UI



Specification

Interfaces

Copper GbE Ports	3
Configurable	
Internal/DMZ/WAN Ports	Yes
Console Ports (RJ45)	1
USB Ports	2

Built-in Wireless LAN

Wireless Standards	IEEE 802.11 a/b/g/n (WEP, WPA, WPA2, 802.11i, TKIP, AES, PSK, 802.1x EAP)
--------------------	---

Antenna	Detachable 3x3 MIMO
---------	---------------------

Access Points	Up to 8 bssid
---------------	---------------

Transmit Power (EIRP)	11n HT40 : +15dBm 11b CCK: +15dBm 11g OFDM: +15dBm
-----------------------	--

Receiver Sensitivity	-68dBm at 300Mbps -70dBm at 54Mbps -88dBm at 6Mbps
----------------------	--

Frequency Range	2.412 GHz - 2.472 GHz 5.200 GHz - 5.825 GHz
-----------------	--

Number of Selectable Channels	USA (FCC) - 11 channels, EU (ETSI) / Japan (TELEC) - 13 channels
-------------------------------	---

Data Rate	802.11n: up to 450Mbps, 802.11b: 1, 2, 5.5, 11Mbps, 802.11g: 6, 9, 12, 18, 24, 36, 48, 54Mbps
-----------	---

System Performance*

Firewall throughput (UDP)	1,000 (Mbps)
Firewall throughput (TCP)	750 (Mbps)
New sessions/second	3,500
Concurrent sessions	60,000
IPSec VPN throughput	110 (Mbps)
No. of IPSec Tunnels	50
SSL VPN Throughput	50 (Mbps)
Anti-Virus throughput	180 (Mbps)
IPS throughput	140 (Mbps)
UTM throughput	80 (Mbps)

Stateful Inspection Firewall

- Layer 8 (User - Identity) Firewall
- Multiple Security Zones
- Access Control Criteria (ACC) - User - Identity, Source & Destination Zone, MAC and IP address, Service
- UTM policies - IPS, Web Filtering, Application Filtering, Anti-Virus, Anti-Spam and Bandwidth Management
- Layer 7 (Application) Control & Visibility
- Access Scheduling
- Policy based Source & Destination NAT
- H.323, SIP NAT Traversal
- 802.1q VLAN Support
- DoS & DDoS Attack prevention
- MAC & IP-MAC filtering and Spoof prevention

Gateway Anti-Virus & Anti-Spyware

- Virus, Worm, Trojan Detection & Removal
- Spyware, Malware, Phishing protection
- Automatic virus signature database update
- Scans HTTP, HTTPS, FTP, SMTP, POP3, IMAP, IM, VPN Tunnels
- Customize individual user scanning
- Scan and deliver by file size
- Block by file types
- Add disclaimer/signature

Gateway Anti-Spam

- Inbound/Outbound Scanning
- Real-time Blacklist (RBL), MIME header check
- Filter based on message header, size, sender, recipient
- Subject line tagging
- IP address Black list/White list
- Redirect Spam mails to dedicated email address
- Image-based Spam filtering using RPD Technology
- Zero hour Virus Outbreak Protection
- IP Reputation-based Spam filtering

Intrusion Prevention System

- Signatures: Default (4500+), Custom
- IPS Policies: Multiple, Custom
- User-based policy creation
- Automatic real-time updates from CRProtect networks
- Protocol Anomaly Detection
- DDoS Attack prevention

Web Filtering

- Inbuilt Web Category Database
- URL, keyword, File type block
- Categories: Default(82+), Custom
- Protocols supported: HTTP, HTTPS
- Block Malware, Phishing, Pharming URLs
- Schedule-based access control
- Custom block messages per category
- Block Java Applets, Cookies, Active X
- CIPA Compliant
- Data leakage control via HTTP, HTTPS upload

Application Filtering

- Inbuilt Application Category Database
- 11+ Application Categories: e.g. Gaming, IM, P2P, Proxy
- Schedule-based access control
- Block
 - P2P applications e.g. Skype
 - Anonymous proxies e.g. Ultra surf
 - "Phone home" activities
 - Keylogger
- Layer 7 (Applications) & Layer 8 (User - Identity) Visibility

Virtual Private Network

- IPSec, L2TP, PPTP
- Encryption - 3DES, DES, AES, Twofish, Blowfish, Serpent
- Hash Algorithms - MD5, SHA-1
- Authentication - Preshared key, Digital certificates
- IPSec NAT Traversal Dead peer detection and PFS support
- Diffie Hellman Groups - 1,2,5,14,15,16
- External Certificate Authority support
- Export Road Warrior connection configuration
- Domain name support for tunnel end points
- VPN connection redundancy
- Overlapping Network support
- Hub & Spoke VPN support

Instant Messaging (IM) Management

- Yahoo and Windows Live Messenger
- Virus Scanning for IM traffic
- Allow/Block Login
- Allow/Block File Transfer
- Allow/Block Webcam
- Allow/Block one-to-one/group chat
- Content-based blocking
- IM activities Log
- Archive files transferred
- Custom Alerts

Wireless WAN

- USB port 3G/4G and Wimax Support
- Primary WAN link
- WAN Backup link

Bandwidth Management

- Application and User Identity based Bandwidth Management
- Guaranteed & Burstable bandwidth policy
- Application & User Identity based Traffic Discovery
- Multi WAN bandwidth reporting
- Category-based bandwidth restriction

User Identity and Group Based Controls

- Access time restriction
- Time and Data Quota restriction
- Schedule based Committed and Burstable Bandwidth
- Schedule based P2P and IM Controls

Networking

- Failover - Automated Failover/Failback, Multi-WAN failover, 3GModem failover
- WRR based load balancing
- Policy routing based on Application and User
- IP Address Assignment - Static, PPPoE, L2TP, PPTP & DDNS Client, Proxy ARP, DHCP server, DHCP relay
- Support for HTTP Proxy
- Dynamic Routing: RIP v1& v2, OSPF, BGP, Multicast Forwarding
- Parent Proxy support with FQDN
- "IPv6 Ready" Gold Logo

Administration & System Management

- Web-based configuration wizard
- Role-based access control
- Firmware Upgrades via Web UI
- Web 2.0 compliant UI (HTTPS)
- UI Color Styler
- Command Line Interface (Serial, SSH, Telnet)
- SNMP (v1, v2c, v3)
- Multi-lingual support: Chinese, Hindi, French, Korean
- Cyberoam Central Console (Optional)
- NTP Support

User Authentication

- Internal database
- Active Directory Integration
- Automatic Windows Single Sign On
- External LDAP/RADIUS database integration
- Thin Client support - Microsoft Windows Server 2003 Terminal Services and Citrix XenApp
- RSA SecurID support
- External Authentication - Users and Administrators
- User/MAC Binding
- Multiple Authentication servers

Logging/Monitoring

- Graphical real-time and historical monitoring
- Email notification of reports, viruses and attacks
- Syslog support
- Log Viewer - IPS, Web filter, Anti Virus, Anti Spam, Authentication, System and Admin Events

IPSec VPN Client**

- Inter-operability with major IPSec VPN Gateways
- Supported platforms: Windows 2000, WinXP 32/64-bit, Windows 2003 32-bit, Windows 2008 32/64-bit, Windows Vista 32/64-bit, Windows 7 RC1 32/64-bit
- Import Connection configuration

Certification

- ICSA Firewall - Corporate
- Checkmark UTM Level 5 Certification
- VPNC - Basic and AES interoperability
- "IPv6 Ready" Gold Logo

Hardware Specifications

Memory	1GB
Compact Flash	4GB

Compliance

- CE
- FCC

Dimensions

H x W x D (inches)	1.7 x 6 x 9.1
H x W x D (cms)	4.4 x 15.3 x 23.2
Weight	1.5kg, 3.307 lbs

Power

Input Voltage	100-240 VAC
Consumption	13.2W
Total Heat Dissipation (BTU)	45

Environmental

Operating Temperature	0 to 40 °C
Storage Temperature	-25 to 75 °C
Relative Humidity (Non condensing)	10 to 90%

*Antivirus, IPS and UTM performance is measured based on HTTP traffic as per RFC 3511 guidelines. Actual performance may vary depending on the real network traffic environments.

Additional purchase required. *Inbound and Outbound Spam filtering cannot be used simultaneously.

Toll Free Numbers

USA : +1-800-686-2360 | India : 1-800-301-00013
APAC/MEA : +1-877-777-0368 | Europe : +44-808-120-3958

Copyright © 1999-2012 Cyberoam Technologies Pvt. Ltd. All Rights Reserved.
Cyberoam and Cyberoam logo are registered trademarks of Elitecore Technologies Ltd. Although Elitecore has attempted to provide accurate information, Elitecore assumes no responsibility for accuracy or completeness of information neither is this a legally binding representation. Elitecore has the right to change, modify, transfer or otherwise revise the publication without notice. AW-10-100252-100423

